



Valves | Water Control Valves (OS&Y and NRS Gate Valves) | **Gate Valves, Outside Screw and Yoke**

# Model K-801-R

## Product Description

Resilient Seated Gate Valves. Rated Working Pressure 300 psi (2068 kPa). Available with the end connections listed below:

## Product Specification

Model No	Valve Size		End Connection
	in	(mm)	
K-801-R	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	Flange × Flange (ANSI, ISO, JIS)

## Details

<b>Category</b>	Gate Valves, Outside Screw and Yoke
<b>Class of Work</b>	1120 - OS&Y and NRS Gate Valves
<b>Approval Standard</b>	FM 1120, 1130 - Fire Service Water Control Valves (OS&Y and NRS Type Gate Valves)
<b>Certification Type</b>	FM Approved
<b>Listing Country</b>	United States of America

## Company

**Kopler LLC**  
501 Silverside Road, STE 105  
4029, Wilmington , Delaware  
19809  
United States of America  
<http://kopler.com>



## Additional Info

### Automatic Sprinkler Systems

---

### Valves

---

### Gate Valves

---

#### Gate Valves, Outside Screw and Yoke

Outside screw and yoke gate valves are recommended for service indoors and in pits outdoors. They are not recommended for throttling service. The stem indicates at a glance whether or not the valve is open. Smaller sizes,  $\frac{3}{4}$  through 2 in. NPS inclusive, are of bronze. Large sizes, 2  $\frac{1}{2}$  through 14 in. NPS inclusive, are of iron, bronze mounted. One manufacturer makes valves of bronze up through the 3 in. size. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

---