

Note: In the process of enhancing our systems, we are transitioning data to a new PiQ data view. This data is being verified with the "Historical" view for accuracy. Once the data is confirmed, the "Historical" view will be discontinued. During this transition, you may encounter duplicate entries or missing/outdated data. For queries during this interim period, please visit our [Historical View FAQs](#) or contact our [Customer Service](#).

Special System Water Control Valves, Pressure-reducing and Pressure-control Type

COMPANY

GRISWOLD INDUSTRIES, DBA CLA-VAL CO

1701 PLACENTIA AVE

COSTA MESA, CA 92627-4416 United States

EX2534

Pilot-operated pressure-control valve, consisting of the following models, types, sizes and pressures:

Model	Body Type	Nominal Pipe Size, NPS	End Configuration*	Max Rated Pressure (psig)	Outlet Pressure-setting Range (psig)
90G-21	Globe	2	Class 150 - F by F	250	30 - 165
90G-21	Globe	1-1/2, 2-1/2, 3, 4, 6, 8, 10, 12	Class 150 - F by F	250	50 - 175
90G-21	Globe	2	Class 300 -F by F, G by G	300	30 - 165
90G-21	Globe	1-1/2, 2-1/2, 3, 4, 6, 8	Class 300 -F by F, G by G	300	50 - 175
90G-21	Globe	10,12	Class 300 F by F	300	50 - 175
90G-21	Globe	2	T by T	300	30 - 165
90G-21	Globe	1-1/2, 2-1/2, 3	T by T	300	50 - 175
90A-21	Angle	2	Class 150 - F by F	250	30 - 165
90A-21	Angle	1-1/2, 2-1/2, 3, 4, 6, 8, 10, 12	Class 150 - F by F	250	50 - 175
90A-21	Angle	2	Class 300 - F by F, G by G, T by T	300	30 - 165
90A-21	Angle	1-1/2, 2-1/2, 3, 4, 6, 8, 10, 12	Class 300 - F by F	300	50 - 175
90A-21	Angle	3, 4	G by G	300	50 - 175

90A-21	Angle	2	T by T	300	30 - 165
90G-21	Angle	1-1/2, 2-1/2, 3	T by T	300	50 - 175

F - Flanged

G - Grooved

T - Threaded

* End configurations are intended to be installed on systems not exceeding end configurations' working capabilities.

The manufacturer's design and installation instructions include a description of the performance characteristics for both flowing and static conditions.

Pressure ratings of components installed downstream shall not be exceeded.

Last Updated on 2022-07-22

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."