

# Models BFV-300, BFV-300C, BFV-250

## Product Description

Model No	Description	Valve Size		Rated Working Pressure		Remarks
		in	(mm)	psi	(kPa)	
BFV-300 Grooved	Butterfly Valve, Grooved Ends	2 1/2, 3, 4, 5, 6	(65, 80, 100, 125, 150)	300	(2065)	a, b, c
BFV-300C Grooved	Butterfly Valve, Grooved Ends	2 1/2, 3, 4, 5, 6	(65, 80, 100, 125, 150)	300	(2065)	a, b, c, e
BFV-300 Grooved	Butterfly Valve, Grooved Ends	8	(200)	300	(2065)	a, b, c
BFV-300C Grooved	Butterfly Valve, Grooved Ends	8	(200)	300	(2065)	a, b, c, e
BFV-300 Wafer	Butterfly Valve, Wafer Body	2 1/2, 3, 4, 5, 6, 8	(65, 80, 100, 125, 150, 200)	300	(2065)	a, b, c
BFV-250 Wafer	Butterfly Valve, Wafer Body	2 1/2, 3, 4, 5, 6, 8	(65, 80, 100, 125, 150, 200)	250	(1720)	a, b, c
BFV-250 Wafer	Butterfly Valve, Wafer Body	10	(250)	175	(1205)	a, b, c
BFV-300 Grooved	Butterfly Valve, Grooved Ends	10	(250)	175	(1205)	a, b, c
BFV-300C Grooved	Butterfly Valve, Grooved Ends	10	(250)	175	(1205)	a, b, c, e
BFV-300 Wafer	Butterfly Valve, Wafer Body	10	(250)	175	(1205)	a, b, c

**Remarks:**

- a. Available with dual supervisory switches.
- b. FM Approved for indoor and outdoor use.
- c. FM Approved for aboveground installations only.
- d. FM Approved indoor service only.
- e. These valves cannot be installed between the fire protection system water source and sprinkler heads. Intended for use in fire pump test bypass lines only..

## Details

<b>Category</b>	Indicating Valves, Butterfly or Ball Type
-----------------	---

## Company

Tyco Fire & Building Products  
 1467 Elmwood Ave, Cranston ,  
 Rhode Island 02910  
 United States of America  
<http://tyco-fire.com>



Member of the FM Global Group

<b>Class of Work</b>	1112 - Indicating Valves
<b>Approval Standard</b>	FM 1112 - Indicating Valves (Butterfly or Ball Type)
<b>Certification Type</b>	FM Approved
<b>Listing Country</b>	United States of America



## Additional Info

### Automatic Sprinkler Systems

---

### Valves

---

### Miscellaneous Valves

---

#### Indicating Valves, Butterfly or Ball Type

Design features provide a dependable visible indication of the open position even at a distance. If excessive force is applied to the handle, weakness-joints will break so as to preserve correct orientation between indicator and valve position. Valve and indicator parts are so designed that they can be assembled only one way, always to give correct indication. All FM Approved indicating valves turn clockwise to shut. They are small, lightweight, and, because of a resilient seat, are easy to operate. They are not subject to sticking or dropped gates. They are not recommended for throttling service. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

---