UL Product iQ®



Model 2050B-4KG1

File Number: EX2855

COMPANY

GRISWOLD INDUSTRIES, DBA CLA-VAL CO 1701 PLACENTIA AVE COSTA MESA, CA 92627-4416 United States

MODEL INFO

2050B-4KG1

ATTRIBUTES AND RATINGS

Body Type	Nom Pipe Size, NPS	End Configuration	Max Relief (Set) Pressure, psig (kPa)
Angle	3, 4, 6, 8	Class 150 - Flanged by Flanged	250 (1723)
Angle	3, 4, 6	Class 300 - Flanged by Flanged, Grooved by Grooved	300 (2068)
Angle	8	Class 300 - Flanged by Flanged	300 (2068)

GENERAL	
nstallation Limitations	
nd configurations are intended to be installed on systems not exceeding end configurations' working capabilitie	S.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."