

# Model DV-5A

File Number: EX6404

**COMPANY**

**TYCO FIRE & BUILDING PRODUCTS**

1467 ELMWOOD AVE  
CRANSTON, RI 02910-3849 United States

**MODEL INFO**

DV-5A

<b>GENERAL</b>						
<b>Sprinkler System Type</b>	<b>Body Type</b>	<b>Nominal Pipe Size, NPS</b>	<b>End Configuration</b>	<b>Max Rated Pressure, psig (kPa)</b>	<b>Trim Configuration Type</b>	<b>Installed Position</b>
Deluge sprinkler system	Globe	1-1/2, 2	Grooved, Threaded	300 (2068)	Dry pilot, Wet pilot, Electric Actuation	Vertical
Deluge sprinkler system	Globe	3, 4, 6, 8	Flanged, Grooved, Flanged by Grooved	300 (2068)	--	Vertical
Deluge sprinkler system	Globe	165.1 mm	Grooved	300 (2068)	--	Vertical
Deluge sprinkler system	Globe	2	Grooved, Threaded	300 (2068)	--	Vertical
Deluge sprinkler system	Globe	3, 4, 6, 8	Flanged, Grooved, Flanged by Grooved	300 (2068)	--	Vertical
Deluge sprinkler system	Globe	165.1 mm	Grooved	300 (2068)	--	Vertical
Deluge sprinkler system	Globe	3, 4, 6, 8	Flanged, Grooved, Flanged by Grooved	250 (1723)	--	Vertical

## GENERAL

<b>Sprinkler System Type</b>	<b>Body Type</b>	<b>Nominal Pipe Size, NPS</b>	<b>End Configuration</b>	<b>Max Rated Pressure, psig (kPa)</b>	<b>Trim Configuration Type</b>	<b>Installed Position</b>
Deluge sprinkler system	Globe	165.1 mm	Grooved	250 (1723)	--	Vertical
Preaction sprinkler system	Globe	1-1/2, 2	Grooved, Threaded	300 (2068)	--	Vertical
Preaction sprinkler system	Globe	3, 4, 6, 8	Flanged, Grooved, Flanged by Grooved	300 (2068)	--	Vertical
Preaction sprinkler system	Globe	165.1 mm	Grooved	300 (2068)	--	Vertical
Preaction sprinkler system	Globe	1-1/2, 2	Grooved, Threaded	300 (2068)	--	Vertical
Preaction sprinkler system	Globe	3, 4, 6, 8	Flanged, Grooved, Flanged by Grooved	300 (2068)	--	Vertical
Preaction sprinkler system	Globe	165.1 mm	Grooved	300 (2068)	--	Vertical

## GENERAL

### Installation Limitations

End configurations are intended to be installed on systems not exceeding end configurations' working capabilities.

For accessories used with these valves, see certifications under Accessories for Special Systems (VLTR).

All trim configuration types shall include a manual release. Height of pilot line above valve limited as shown in the installation instructions.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."

