

Model 55L-60

Product Description

Model No	Valve Size		Rated Working Pressure		Remarks
	in	(mm)	psi	(kPa)	
Model 55L-60	1/2, 3/4	(15, 20)	300	(2065)	a, b, c, d

Remarks:

- a. Valve supplied with Female NPT inlet and outlet connection.
- b. Adjustable relief pressure settings from 0 to 75, 20 to 200, or 100 to 300 psi (0 to 515, 140 to 1380, or 690 to 2070 kPa).
- c. Approved when supplied with either a stainless steel or bronze valve body.
- d. Not suitable for discharging the full rated pump capacity.

Details

Category	Trim Water Pressure Relief Valves, Adjustable
Class of Work	1359 - Trim Water PRV (1/4th2-1/2)
Approval Standard	FM 1359 - Trim Water Pressure Relief Valves 1/4 Inch Through 2 1/2 Inch Nominal Size
Certification Type	FM Approved
Listing Country	Switzerland

Company

Cla-Val Europe
 Chemin des Mesanges 1, 1032
 Romanel-sur-Lausanne,
 Switzerland
<http://cla-val.ch>



Member of the FM Global Group

Additional Info

Automatic Sprinkler Systems

Valves

Miscellaneous Valves

Trim Water Pressure Relief Valves, Adjustable

An adjustable set pressure trim water pressure relief valve is a small valve designed to relieve pressure build-up in a sprinkler system or in valve trim. It is open to a drain line. Unless otherwise specified, rated working pressure is 175 psi (1205 kPa). The range of pressure setting is shown below.
